

# Excellent maneuverability for large surfaces.

The range of B 80 W BP scrubbers are large but still easily maneuverable. With a robust and maintenance-friendly brush head, they are available with roller or disc brushes in 22", 26" and 30" working widths.



1 4-color LCD display

- All cleaning programs are indicated by large easy-to-read symbols on the large 4-color display, along with all major functions: battery capacity with remaining running time in minutes, water quantity, cleaning or transport speed, service interval indicator, dirty water tank full and cleaning agent dosage in percent.

2 Automatic lowering and raising of cleaning head and squeegee

- The cleaning head and squeegee are raised automatically for reverse travel and lowered again when you change back to forward travel. This easy and convenient operation save wear and tear on both the cleaning head and squeegee.

3 Automatic water filling (optional)

- The Auto Fill In option allows the B 80 to fill with fresh B 80 W. To fill, simply

connect a hose with a conventional quick coupling. Filling stops automatically when the tank is full. During filling time the operator can perform other tasks, saving time and money.

4 Flexible Application Control Technology (FACT)

- With FACT technology, a Kärcher exclusive, the brush speed of roller brushes can be adjusted to different cleaning applications using three settings. Power Clean 100% - for stubborn dirt and polishing. Whisper Clean 60% - reduces noise

levels and ensures long working intervals with low power consumption. Fine Clean 40%, the grey film on so-called fine stoneware tiles can optimally be removed in conjunction with the green roller.

# Technical data and equipment.



**B 80 W BP + R 65**

**B 80 W BP + R 75**

**B 80 W BP + D 65**

**B 80 W BP + D 75**

## TECHNICAL SPECIFICATIONS

Cleaning path/width	in	26	30	26	30
Brush type	cylindrical/disc/pad	Cylindrical	Cylindrical	Disc	Disc
Brush quantity	units	2	2	2	2
Suction bar (squeegee) width	in	39	39	39	39
Drive	pad-assist/traction	Traction	Traction	Traction	Traction
Solution/recovery capacity	gal	21/21	21/21	21/21	21/21
Theoretical / practical productivity	ft <sup>2</sup> / h	27,980 / 18,180	32,290 / 21,000	27,980 / 18,180	32,290 / 21,000
Operating noise level - std / Eco! mode	dBA	69 / 66	69 / 66	69 / 66	69 / 66
Battery charger	shelf/on-board	On-Board	On-Board	On-Board	On-Board
Brush contact pressure	lbs	213	213	117	136
Brush speed	rpm	400-1,550	400-1,550	180	180
Drive/vac motor rating	watts	350 / 580	350 / 580	350 / 580	350 / 580
Vac motor suction	cfm	53	53	53	53
Waterlift	in of water	67	67	67	67
Weight (excl. battery / with battery)	lbs	282 / 617	284 / 617	289 / 617	293 / 617
Dimensions (L x W x H)	in	61 x 29 x 45	61 x 32 x 45	62 x 29 x 45	64 x 32 x 45

## EQUIPMENT

Order No.	Description
9.841-197.0	B 80 W Bp, scrub deck sold separately, 24V/225 Ah wet batteries, on-board charger, with curved squeegee
9.841-202.0	B 80 W Bp, scrub deck sold separately, 24V/260 Ah wet batteries, on-board charger, with curved squeegee
-	B 80 W Bp, R 75 and D 75 decks are ordered separately
9.841-196.0	B 80 W Bp, D 65 disc scrub deck, batteries and charger sold separately, with curved squeegee
9.841-195.0	B 80 W Bp, R 65 cylindrical scrub deck, batteries and charger sold separately, with curved squeegee
9.841-199.0	B 80 W Bp, scrub deck sold separately, 24V/255 Ah AGM batteries, on-board charger, with curved squeegee
9.841-388.0	B 80 W Bp, D 65 disc scrub deck, 24V/225 Ah wet batteries
9.841-204.0	B 80 W Bp, D 65 disc scrub deck, 24V/260 Ah wet batteries, with curved squeegee
9.841-198.0	B 80 W Bp, R 65 cylindrical scrub deck, 24V/225 Ah wet batteries, on-board charger, with curved squeegee
9.841-200.0	B 80 W Bp, R 65 cylindrical scrub deck, 24V/255 Ah AGM batteries, on-board charger, with curved squeegee
9.841-201.0	B 80 W Bp, D 65 disc scrub deck, 24V/255 Ah AGM batteries, on-board charger, with curved squeegee
9.841-203.0	B 80 W Bp, R 65 cylindrical scrub deck, 24V/260 Ah wet batteries, on-board charger, with curved squeegee

## ACCESSORIES

Order No.	Description
☑ 4.777-080.0	Squeegee assembly, 39-inch, V-shaped polyurethane oil-resistant blades, standard on machines with R 75 & D 75 scrub decks
☑ 5.035-488.0	Home Base kit (adapter and cable hook)
☑ 6.980-077.0	Double hook (requires 5.035-488.0)
☑ 8.600-251.0	Cable asm, bat. Jumper x 15" (required w/ no battery units)
☑ 4.035-345.0	Quick fill tank system (requires 9.083-003.0)
☑ 9.083-003.0	Hose coupling
☑ 6.273-205.0	Squeegee blade set, anti stripe oil resistant
☑ 6.273-291.0	Squeegee blade set, for textured floors
☑ 4.035-408.0	KIK Key

SERVICES

Order No.	Description
☑ 7.000-270.0	Fleet one year premium subscription

---

☑ Included ☑ Optional