

We make the system. They make the attachments.

At Kärcher, we are concerned about your health and safety. We think that it is important to get the vacuum system down perfectly first. Our competition only seems to be concerned with the tool attachments. The new generation of Tact wet and dry vacuums are high-performing units that pack a lot of features. Thanks to our continuous improvements to our automatic cleaning system (Tact), large amounts of fine dusts can be vacuumed without any interruption in suction. Vacuum performance remains at the same high level you have come to expect from Kärcher wet/dry vacs. There is no need of manual filter cleaning. It is fully compliant with the new OSHA silica dust regulations and models NT 30/1, NT 40/1 and NT 50/1 carry a lifetime warranty on the tank and vacuum motor. The perfect solution for demanding customers in the rental, construction, industrial and automotive industries. We make the best wet and dry vacuum cleaners on the market!



1 Filtration system

- Improved Tact automatic filter cleaning system for improved cleaning performance and reduced noise level
- Fully compliant with the new OSHA silica dust regulations
- HEPA filter is standard with NT 30/1, NT 40/1 & NT 50/1

2 Robust design

- Even stronger and sturdier components and overall design
- Large metal caster wheels for easier usage at construction sites

3 Improved accessories on NT 30/1, NT 40/1 & NT 50/1

- Accessory system improves performance and usability
- Bayonet and clip connections guarantee easy and secure connection of all accessory parts onto machine
- The new bend with rubber grip area has an ergonomic design for comfortable working conditions.

4 Easier to use NT 30/1, NT 40/1 & NT 50/1

- Easy handling: EASY! Operation Switch, integrated accessory storage
- Large net volume and easy handling thanks to convenient location of vacuum hose connector
- Flat vacuum head with power tool box fixation options
- Wider inner diameter of vacuum hoses 1-3/8 inches (DN 35) standard

WARNING: This product can expose you to chemicals including lead and Diisononyl phthalate, which are known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov

Technical data and equipment.

NT 30/1 TACT TE

NT 40/1 TACT TE

NT 50/1 TACT TE

TECHNICAL SPECIFICATIONS

Air flow rate	cfm	150	150	150
Water lift	in	102	102	102
Container capacity	gal	8.2	10.3	13.5
Max. power rating	W	1380	1380	1380
Sound pressure level	dBA	68	68	68
Weight	lbs	30.0	32	40
Cord length	ft	25	25	25
Vac hose		1-3/8" x 13 ft	1-3/8" x 13 ft	1-3/8" x 13 ft
Dimensions (L x W x H)	in	22 x 14.5 x 22.2	22 x 14.5 x 25.7	25.1 x 14.5 x 41.1

EQUIPMENT

Order No.	Description
1.148-216.0	NT 30/1 Tact Te
1.148-316.0	NT 40/1 Tact Te
1.148-416.0	NT 50/1 Tact Te

ACCESSORIES

Order No.	Description
2.889-192.0	Stainless steel vacuum tube set
2.889-135.0	Vacuum hose 13 ft (Te versions)
2.889-134.0	Vacuum hose 8 ft (30/1 Tact L)
2.889-170.0	Ergonomic bend
2.889-152.0	Wet and dry floor nozzle
2.889-159.0	Crevice nozzle
2.889-151.0	Power tool adaptor (Te versions)
2.889-154.0	Fleece filter bags 30 L for both 30/1 models
2.889-155.0	Fleece filter bags for 40/1 & 50/1
6.907-629.0	HEPA filter (included with NT 30/1, NT 40/1, NT 50/1)
2.889-137.0	Vacuum hose 1-3/8 inch diameter (DN 35) 13 ft electrically conductive
2.889-136.0	Vacuum hose 1-3/8 inch diameter (DN 35) 8 ft electrically conductive
2.889-164.0	Vacuum hose 1-3/8 inch diameter (DN 35) 8 ft heat-resistant
2.889-172.0	Ergonomic bend 1-3/8 inch diameter (DN 35) with soft grip electrically conductive
2.889-148.0	Ergonomic bend 1-3/8 inch diameter (DN 35) with soft grip and vacuum power regulation
6.907-455.0	Flat pleated filter PTFE
2.679-000.0	Drilling dust nozzle 1-3/8 inch diameter (DN 35)
2.643-868.0	Push handle for NT 40/1 Tact Te L
2.889-138.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft
2.889-139.0	Vacuum hose 1-5/8 inch diameter (DN 40), 8 ft
2.889-141.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft electrically conductive
2.889-140.0	Vacuum hose 1-5/8 inch diameter (DN 40), 13 ft oil-resistant
2.889-171.0	Ergonomic bend 1-5/8 inch diameter (DN 40), with soft grip
2.889-172.0	Ergonomic bend 1-5/8 inch diameter (DN 40), with soft grip electrically conductive
2.889-194.0	Set of vacuum tubes 1-5/8 inch diameter (DN 40), 2 x 1.8 ft, stainless steel
6.907-629.0	HEPA filter for NT 30/1, NT 40/1 & NT 50/1
2.889-174.0	Wide wet and dry floor nozzle with easily changeable inserts for wet/dry applications
5.453-042.0	Power tool adapter, fits these size shrouds: 1.06" – 1.10" OD, 1.25" – 1.32" OD, 1.37" – 1.44" OD, 1.47" – 1.50" OD
5.453-016.0	Power tool adapter, fits these size shrouds: 1.06" – 1.07" OD, 1.27" – 1.30" OD, 1.40" – 1.41" OD
5.407-108.0	Power tool adapter: connects to 40 mm hose connection, screws into 35 mm hose or 5.453-016.0 tool adapter
2.637-217.0	Power tool "Y" adapter
5.453-085.0	Power tool adapter sleeve 40 x 50 mm
5.031-703.0	Tension ring (order with 5.407-113.0)
5.407-113.0	Reducer, DN 40 to DN 35 hose connection

Included Optional